

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes PU Speedcoat Comp. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
 - SU19 Building and construction work
- Product category
 - PC9a Coatings and paints, thinners, paint removers
 - PC35 Washing and cleaning products (including solvent based products)
 - PC0 Other
- Process category
 - PROC11 Non industrial spraying
 - PROC7 Industrial spraying
 - PROC19 Manual activities involving hand contact
 - PROC10 Roller application or brushing
- Environmental release category
 - ERC5 Use at industrial site leading to inclusion into/onto article
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category
 - AC11 Wood articles
 - AC7 Metal articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 1)



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Additional information: For professional use only.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



GHS02



GHS07

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 2)

· Dangerous components:		
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29	n-butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066	25-50%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics. (Note-P) ⚠ Flam. Liq. 3, H226 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ STOT SE 3, H336	2.5-10%
CAS: 110-43-0 EINECS: 203-767-1 Index number: 606-024-00-3 Reg.nr.: 01-2119902391-49	heptan-2-one ⚠ Flam. Liq. 3, H226 ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; STOT SE 3, H336	≤2.5%
CAS: 1065336-91-5 EC number: 915-687-0 Reg.nr.: 01-2119491304-40-0000	Reaction mass of bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate and methyl 1,2,2,6,6-pentamethyl-4-piperidyl sebacate ⚠ Aquatic Acute 1, H400; Aquatic Chronic 1, H410 ⚠ Skin Sens. 1A, H317	≥0.25-<1%
CAS: 97-86-9 EINECS: 202-613-0 Index number: 607-113-00-X Reg.nr.: 01-2119488331-38	isobutyl methacrylate ⚠ Flam. Liq. 3, H226 ⚠ Skin Irrit. 2, H315; Skin Sens. 1B, H317; STOT SE 3, H335	≥0.1-<0.3%
CAS: 868-77-9 EINECS: 212-782-2 Index number: 607-124-00-X Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥0.1-<0.3%
CAS: 80-62-6 EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	methyl methacrylate ⚠ Flam. Liq. 2, H225 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	≥0.1-<0.3%

· Additional information:

Note P: The substance does not have to be classified as a carcinogen or mutagen as can be shown that the substance contains less than 0.1% (w / w) benzene (EINECS No 200-753-7.). This note applies only to certain complex oil-derived substances in Part 3.

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 3)
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

* **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

* **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 4)

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate		
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
110-43-0 heptan-2-one		
WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk	
80-62-6 methyl methacrylate		
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm	
123-86-4 n-butyl acetate		
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
110-43-0 heptan-2-one		
WEL	Short-term value: 475 mg/m ³ , 100 ppm Long-term value: 237 mg/m ³ , 50 ppm Sk	
80-62-6 methyl methacrylate		
WEL	Short-term value: 416 mg/m ³ , 100 ppm Long-term value: 208 mg/m ³ , 50 ppm	

- Regulatory information WEL: EH40/2020

· DNEL (Derived No Effect Level) voor professionals		
123-86-4 n-butyl acetate		
Dermal	Short-term - systemic effects.	11 mg/kg (Employees)
	Long-term - systemic effects.	11 mg/kg/day (Employees)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 5)

Inhalative	Long-term - local effects. Short-term systemic effects. Short term - local effects. Long-term - systemic effects.	300 mg/m ³ (Employees) 600 mg/m ³ (Employees) 600 mg/m ³ (Employees) 300 mg/m ³ (Employees)
64742-95-6 Hydrocarbons, C9, aromatics. (Note-P)		
Oral	Long-term - systemic effects.	11 mg/kg/day (General population)
Dermal	Long-term - systemic effects. Long-term systemic effects.	25 mg/kg/day (Industry) 11 mg//kg/day (General population)
Inhalative	Long-term - systemic effects. Long-term - systemic effects. Long-term exposure (8 hours TWA) 19 ppm	32 mg/m ³ (General population) 150 mg/m ³ (Industry) 100 mg/m ³ (Occupational exposure limits)
110-43-0 heptan-2-one		
Oral	Long-term - systemic effects.	23.32 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	84.31 mg/m ³ (General population)
80-62-6 methyl methacrylate		
Dermal	Long-term - systemic effects.	13.67 mg/kg/day (Employees)
Inhalative	Acute / short term - local defects Long-term - local effects. Long-term - systemic effects.	416 mg/m ³ (Employees) 208 mg/m ³ (Employees) 348.4 mg/m ³ (Employees)
· DNEL (Derived No Effect Level) for general audience		
123-86-4 n-butyl acetate		
Oral	Long-term systemic effects. Short-term - systemic effects.	2 mg/kg bw/day (General population) 6 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects. Long-term - local effects.	6 mg/kg bw/day (General population) 35.7 mg/m ³ (General population)
Inhalative	Short-term - systemic effects. Long-term - systemic effects. Short-term - systemic effects. Short-term - local effects.	6 mg/kg (General population) 35.7 mg/m ³ (General population) 300 mg/kg (General population) 300 mg/m ³ (General population)
110-43-0 heptan-2-one		
Dermal	Long-term - systemic effects.	54.27 mg/kg bw/day (Employees)
Inhalative	Acute - systemic effects. Long-term - systemic effects. Long term - systemic effects.	1,516 mg/m ³ (Employees) 394.25 mg/m ³ (Employees) 23.32 mg/kg bw/day (General population)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 6)

80-62-6 methyl methacrylate

Oral	Long-term systemic effects.	8.2 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	8.2 mg/kg bw/day (General population)
	Long-term - local effects.	1.5 mg/m ³ (General population)
Inhalative	Long-term - systemic effects.	74.3 mg/m ³ (General population)
	Long-term - local effects.	104 mg/m ³ (General population)

· PNECs

123-86-4 n-butyl acetate

Aquatic compartment.	0.18 mg/l (Freshwater)
Aquatic compartment.	0.018 mg/l (Seawater)
STP	35.6 mg/l (Segmentation, Targeting and Positioning)
Soil	0.981 mg/kg (Freshwater)
Intermittent	0.36 mg/l (Intermittent)
Soil	0.0903 mg/kg (soil)
Sediment	0.0981 mg/kg (Seawater)

110-43-0 heptan-2-one

Fresh water sedimentation	1.89 mg/kg (Freshwater)
Sea water sedimentation	0.189 mg/kg (Seawater)
Aquatic compartment.	0.0982 mg/l (Freshwater)
	0.982 mg/l (Intermittent)
Aquatic compartment.	0.00982 mg/l (Seawater)
STP	12.5 mg/l (Segmentation, Targeting and Positioning)
Soil	0.321 mg/kg (soil)

80-62-6 methyl methacrylate

Aquatic compartment.	0.94 mg/l (Freshwater)
Aquatic compartment.	0.094 mg/l (Seawater)
STP	10 mg/l (Segmentation, Targeting and Positioning)
Soil	10.2 mg/kg (Freshwater)
Soil	1.48 mg/kg (soil)
Sediment	0.102 mg/kg (Seawater)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
- Respiratory protection:
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 7)

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.

- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: PE gloves, recommended film thickness:> 0.7 mm.

For a touch of 30-120 minutes: gloves made of PVA, recommended material thickness: 0.7 mm.

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

- As protection from splashes gloves made of the following materials are suitable:

Gloves of nitrile rubber, recommended material thickness:> 0.3 mm,
neoprene or butyl rubber, recommended material thickness:> 0.4 mm.

- Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

- 9.1 Information on basic physical and chemical properties

- General Information

- Physical state

Fluid

- Colour:

According to product specification

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 8)

· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	124-128 °C (123-86-4 n-butyl acetate)
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	1.2 Vol % (123-86-4 n-butyl acetate)
· Upper:	7.5 Vol % (123-86-4 n-butyl acetate)
· Flash point:	24 °C
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity at 20 °C	40 s (DIN 53211/4)
· Dynamic:	Not determined.
· Solubility	
· water:	Fully miscible.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-butyl acetate)
· Density and/or relative density	
· Density at 20 °C:	1.042 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information	
· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Ignition temperature:	370 °C (123-86-4 n-butyl acetate)
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	41.1 %
· VOC content:	41.13 %
	VOC content:
	428.6 g/l / 3.58 lb/gal
· Solids content:	58.9 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes	
· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Flammable liquid and vapour.

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 9)

- | | |
|---|------|
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

- LD/LC50 values relevant for classification:

123-86-4 n-butyl acetate

Oral	LD50	13,100 mg/kg bw (rat)
Dermal	LD50	>5,000 mg/kg bw (rabbit)
Inhalative	LC50/4 h	>21 mg/l (rat)

110-43-0 heptan-2-one

Oral	LD50	1,670 mg/kg bw (rat)
Dermal	LD50	12,600 mg/kg bw (rabbit)
	Short-term exposure (15 minutes): 100 ppm	475 mg/m ³ (Occupational exposure limits)

97-86-9 isobutyl methacrylate

Oral	LD50	11,990 mg/kg bw (mouse)
------	------	-------------------------

868-77-9 2-hydroxyethyl methacrylate

Oral	LD50	5,050 mg/kg bw (rat)
------	------	----------------------

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 10)

80-62-6 methyl methacrylate

Oral	LD50	7,872 mg/kg bw (rat)
Dermal	Acute / short-term - local effects.	1.5 mg/cm ² (Employees)
	Long-term - local effects.	1.5 mg/cm ² (Employees)

- STOT-single exposure May cause drowsiness or dizziness.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

GB

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022



Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 11)

SECTION 14: Transport information

<ul style="list-style-type: none"> · 14.1 UN number or ID number · ADR, IMDG, IATA 	<p>UN1263</p>
<ul style="list-style-type: none"> · 14.2 UN proper shipping name · ADR · IMDG, IATA 	<p>1263 PAINT PAINT</p>
<ul style="list-style-type: none"> · 14.3 Transport hazard class(es) · ADR 	<div style="text-align: center;">  </div> <p>Class 3 (F1) Flammable liquids. Label 3</p> <hr style="border-top: 1px dashed black;"/> <div style="text-align: center;">  </div> <p>Class 3 Flammable liquids. Label 3</p>
<ul style="list-style-type: none"> · IMDG, IATA 	
<ul style="list-style-type: none"> · 14.4 Packing group · ADR, IMDG, IATA 	<p>III</p>
<ul style="list-style-type: none"> · 14.5 Environmental hazards: 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category 	<p>Warning: Flammable liquids. 30 F-E, S-E A</p>
<ul style="list-style-type: none"> · 14.7 Maritime transport in bulk according to IMO instruments 	<p>Not applicable.</p>
<ul style="list-style-type: none"> · Transport/Additional information: 	
<ul style="list-style-type: none"> · ADR · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml</p>
<ul style="list-style-type: none"> · Transport category · Tunnel restriction code 	<p>3 D/E</p>
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	<p>5L Code: E1 Maximum net quantity per inner packaging:</p>

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 12)

·	30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
- National regulations:
- Technical instructions (air):

Class	Share in %
NK	25-50
- Waterhazard class:
Water hazard class 1 (Self-assessment): slightly hazardous for water.
- 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
 - H225 Highly flammable liquid and vapour.
 - H226 Flammable liquid and vapour.
 - H302 Harmful if swallowed.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H332 Harmful if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H411 Toxic to aquatic life with long lasting effects.
 - EUH066 Repeated exposure may cause skin dryness or cracking.
- Department issuing SDS: Research & Development.

(Contd. on page 14)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 10 (replaces version 9)

Revision: 04.02.2022

Trade name: Epifanes PU Speedcoat Comp. A

(Contd. of page 13)

- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 2: Flammable liquids - Category 2
 - Flam. Liq. 3: Flammable liquids - Category 3
 - Acute Tox. 4: Acute toxicity - Category 4
 - Skin Irrit. 2: Skin corrosion/irritation - Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
 - Skin Sens. 1: Skin sensitisation - Category 1
 - Skin Sens. 1A: Skin sensitisation - Category 1A
 - Skin Sens. 1B: Skin sensitisation - Category 1B
 - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 - Asp. Tox. 1: Aspiration hazard - Category 1
 - Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1
 - Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
- * Data compared to the previous version altered.