

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

**SECTION 1: Identification of the substance/mixture and of the company/
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy Primer Comp. A
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
 - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
 - SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category
 - ERC8c Widespread use leading to inclusion into/onto article (indoor)
 - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
 - ERC5 Use at industrial site leading to inclusion into/onto article
- Article category AC7 Metal articles
- Application of the substance / the mixture
See our technical datasheet for application of this product.
base component of a two-component primer
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:
W.Heeren & Zoon bv.
P.O. box 166
1430 AD Aalsmeer
Netherlands
tel.+31-(0)297-360366
email: r&d@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number:
W.Heeren & Zoon bv. tel: +31 297 360678, E-mail: rend@epifanes.nl
Office hours: weekdays from 08:00 to 17:00.
The National Poisons Information Service; dial 111
Solely intended to inform professionals in acute poisoning!

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008
The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



GHS02 GHS07

- Signal word Warning
- Hazard-determining components of labelling:
phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bis[oxirane]
- Hazard statements
H226 Flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.
- Precautionary statements
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Additional information:
Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- 3.2 Mixtures
- Description:
Resin mixture
Solvent mixture with pigment additives

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 2)

Dangerous components:

CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	10-25%
CAS: 25036-25-3 EC number: 607-500-3	phenol, 4,4'-(1-methylethylidene)bis-, polymer with 2,2'-[(1-methylethylidene) bis(4,1-phenyleneoxymethylene)] bis[oxirane] Aquatic Chronic 2, H411 Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	≥10-<25%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%
CAS: 77-99-6 EINECS: 201-074-9 Reg.nr.: 01-2119486799-10	propylidynetrimethanol Repr. 2, H361fd	<0.3%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation:
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:
Immediately wash with water and soap and rinse thoroughly.
Immediately rinse with water.
- After eye contact:
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 3)

* **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- Suitable extinguishing agents:
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture
During heating or in case of fire poisonous gases are produced.
No further relevant information available.
- 5.3 Advice for firefighters
- Protective equipment:
Wear fully protective suit.
Mouth respiratory protective device.

* **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures
Wear protective clothing.
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
Prevent seepage into sewage system, workpits and cellars.
Inform respective authorities in case of seepage into water course or sewage system.
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- 6.4 Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* **SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling
Keep away from heat and direct sunlight.
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- Information about fire - and explosion protection:
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 4)

- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles:
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

- Ingredients with limit values that require monitoring at the workplace:

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
-----	-------------------------------------------------------------------------------------------------------------

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	------------------------------------------------------------------------------------------------------------------

107-98-2 1-methoxy-2-propanol

WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
-----	-------------------------------------------------------------------------------------------------------------

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	------------------------------------------------------------------------------------------------------------------

- Regulatory information WEL: EH40/2020

- DNEL (Derived No Effect Level) voor professionals

107-98-2 1-methoxy-2-propanol

Oral	Long-term - systemic effects.	33 mg/kg/day (General population)
Dermal	Long-term - systemic effects.	183 mg/kg/day (Industry)
	Long-term systemic effects.	78 mg//kg/day (General population)
Inhalative	Long-term - systemic effects.	43.9 mg/m ³ (General population)
	Long-term - local effects.	369 mg/m ³ (Employees)
	Long-term - systemic effects.	43.9 mg/m ³ (General population)
	Short-term systemic effects.	553.5 mg/m ³ (Industry)
	Short term - local effects.	553.5 mg/m ³ (Industry)
	Long-term - systemic effects.	369 mg/m ³ (Industry)

1330-20-7 Xylene

Oral	Long-term - systemic effects.	1.6 mg/kg bw/day (General population)
Inhalative	Long-term - local effects.	77 mg/m ³ (Employees)

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 5)

	Acute - systemic effects.	174 mg/m ³ (General population)
	Long-term - systemic effects.	14.8 mg/m ³ (General population)
77-99-6 propylidynetrimehanol		
Oral	Long-term - systemic effects.	0.34 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.58 mg/m ³ (General population)
· DNEL (Derived No Effect Level) for general audience		
107-98-2 1-methoxy-2-propanol		
Oral	Acute - systemic effects	553.5 mg/kg (Employees)
Dermal	Long-term - systemic effects.	50.6 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	369 mg/m ³ (Employees)
	Long term - systemic effects.	18.1 mg/kg bw/day (General population)
1330-20-7 Xylene		
Oral	Acute - systemic effects	289 mg/kg (Employees)
Dermal	Long-term - systemic effects.	180 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	77 mg/m ³ (Employees)
	Short-term - systemic effects.	289 mg/kg (Employees)
	Short-term - local effects.	174 mg/m ³ (General population)
	Long term - systemic effects.	108 mg/kg bw/day (General population)
77-99-6 propylidynetrimehanol		
Dermal	Long-term - systemic effects.	0.94 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	3.3 mg/m ³ (Employees)
	Long term - systemic effects.	0.34 mg/kg bw/day (General population)

· PNECs

107-98-2 1-methoxy-2-propanol

Sewage treatment plant	100 mg/l (Sewage treatment plant)
Aquatic compartment.	10 mg/l (Freshwater)
Aquatic compartment.	1 mg/l (Seawater)
Soil	5.2 mg/kg (Seawater)
	52.3 mg/kg (Freshwater)
Intermittent	100 mg/l (Intermittent)
Soil	4.59 mg/kg (soil)

1330-20-7 Xylene

Sewage treatment plant	6.58 mg/l (Sewage treatment plant)
Aquatic compartment.	0.327 mg/l (Freshwater)
Aquatic compartment.	0.327 mg/l (Seawater)
Aquatic compartment - water, intermittent releases	0.327 mg/L (Freshwater)
Soil	12.46 mg/kg (Seawater)

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 6)

Soil	12.46 mg/kg (Freshwater)
	2.31 mg/kg (soil)

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV 650 mmol/mol creatinine
Medium: urine
Sampling time: post shift
Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

· Respiratory protection:

Suitable respiratory protective device recommended.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter AX

In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 7)

- Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

- General Information
- Physical state Fluid
- Colour: According to product specification
- Odour: Characteristic
- Odour threshold: Not determined.
- Melting point/freezing point: Undetermined.
- Boiling point or initial boiling point and boiling range 36 °C (1330-20-7 Xylene)
- Flammability Not applicable.
- Lower and upper explosion limit
- Lower: 2.3 Vol % (107-98-2 1-methoxy-2-propanol)
- Upper: ~20 Vol % (107-98-2 1-methoxy-2-propanol)
- Flash point: 26 °C
- Auto-ignition temperature: Product is not selfigniting.
- Decomposition temperature: Not determined.
- pH Not determined.
- Viscosity:
- Kinematic viscosity at 20 °C 100 s (DIN 53211/4)
- Dynamic: Not determined.
- Solubility
- water: Fully miscible.
- Partition coefficient n-octanol/water (log value) Not determined.
- Vapour pressure at 20 °C: 12 hPa (107-98-2 1-methoxy-2-propanol)
- Density and/or relative density
- Density at 20 °C: 1.734 g/cm³
- Relative density Not determined.
- Vapour density Not determined.

· 9.2 Other information

- Appearance:
- Form: Fluid
- Important information on protection of health and environment, and on safety.
- Ignition temperature: 270 °C
- Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 8)

- Solvent content:
- Organic solvents: 25.3 %
- VOC content: 25.31 %
- VOC content:
438.9 g/l / 3.66 lb/gal
- Solids content: 74.7 % (VB% 1h150 C)
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:
No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity

· LD/LC50 values relevant for classification:

107-98-2 1-methoxy-2-propanol

Oral	LD50	5,660 mg/kg bw (rat)
------	------	----------------------

(Contd. on page 10)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 9)

Dermal	LD50	13,000 mg/kg bw (rabbit)
	Short-term exposure (15 minutes): 100 ppm	563 mg/m ³ (Occupational exposure limits)
	Long-term exposure (8 hours TWA): 50 ppm	375 mg/m ³ (Occupational exposure limits)
Inhalative	LC50/4 h	6 mg/l (rat)
1330-20-7 Xylene		
Dermal	Short-term exposure (15 minutes): 100 ppm	442 mg/m ³ (Occupational exposure limits)
	Long-term exposure (8 hours TWA): 50 ppm	221 mg/m ³ (Occupational exposure limits)
77-99-6 propylidynetrimethanol		
Oral	LD50	14,100 mg/kg bw (rat)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- 11.2 Information on other hazards

- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Harmful to fish
- Additional ecological information:
- General notes:
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- 13.1 Waste treatment methods
- Recommendation
Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)



Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 10)

- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:
Water, if necessary together with cleansing agents.

SECTION 14: Transport information

- 14.1 UN number or ID number
· ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name
· ADR 1263 PAINT
· IMDG, IATA PAINT
- 14.3 Transport hazard class(es)
· ADR

· Class 3 (F1) Flammable liquids.
· Label 3
- IMDG, IATA

· Class 3 Flammable liquids.
· Label 3
- 14.4 Packing group
· ADR, IMDG, IATA III
- 14.5 Environmental hazards:
· Marine pollutant: No
- 14.6 Special precautions for user Warning: Flammable liquids.
· Hazard identification number (Kemler code): 30
· EMS Number: F-E, S-E
· Stowage Category E
- 14.7 Maritime transport in bulk according to IMO instruments Not applicable.
- Transport/Additional information:
· ADR
· Limited quantities (LQ) 5L
· Excepted quantities (EQ) Code: E1
Maximum net quantity per inner packaging:
30 ml
Maximum net quantity per outer packaging:

(Contd. on page 12)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 11)

·	1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	> 450 l: 3 F1, III

· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	> 450 l: 3, III
· UN "Model Regulation":	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
 - Directive 2012/18/EU
 - Named dangerous substances - ANNEX I None of the ingredients is listed.
 - Seveso category P5c **FLAMMABLE LIQUIDS**
 - Qualifying quantity (tonnes) for the application of lower-tier requirements
5,000 t
 - Qualifying quantity (tonnes) for the application of upper-tier requirements
50,000 t
 - National regulations:
 - Technical instructions (air):
- | Class | Share in % |
|-------|------------|
| NK | 25-50 |
- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
 - 15.2 Chemical safety assessment:
A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.02.2022

Version number 11 (replaces version 10)

Revision: 04.02.2022

Trade name: Epifanes Epoxy Primer Comp. A

(Contd. of page 12)

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

- Department issuing SDS: Research & Development.
- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl
- Abbreviations and acronyms:
 - RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
 - ICAO: International Civil Aviation Organisation
 - ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances
 - ELINCS: European List of Notified Chemical Substances
 - CAS: Chemical Abstracts Service (division of the American Chemical Society)
 - VOC: Volatile Organic Compounds (USA, EU)
 - DNEL: Derived No-Effect Level (REACH)
 - PNEC: Predicted No-Effect Concentration (REACH)
 - LC50: Lethal concentration, 50 percent
 - LD50: Lethal dose, 50 percent
 - PBT: Persistent, Bioaccumulative and Toxic
 - vPvB: very Persistent and very Bioaccumulative
 - Flam. Liq. 3: Flammable liquids - Category 3
 - Acute Tox. 4: Acute toxicity - Category 4
 - Skin Irrit. 2: Skin corrosion/irritation - Category 2
 - Eye Irrit. 2: Serious eye damage/eye irritation - Category 2
 - Skin Sens. 1: Skin sensitisation - Category 1
 - Repr. 2: Reproductive toxicity - Category 2
 - STOT SE 3: Specific target organ toxicity (single exposure) - Category 3
 - STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2
 - Asp. Tox. 1: Aspiration hazard - Category 1
 - Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2
 - Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3
- * Data compared to the previous version altered.

None