

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

**SECTION 1: Identification of the substance/mixture and of the company/  
undertaking**

- 1.1 Product identifier
- Trade name: Epifanes Epoxy Primer Comp. B (cure)
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use
  - SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
  - SU21 Consumer uses: Private households / general public / consumers
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC10 Roller application or brushing
- Environmental release category
  - ERC5 Use at industrial site leading to inclusion into/onto article
  - ERC8c Widespread use leading to inclusion into/onto article (indoor)
  - ERC8f Widespread use leading to inclusion into/onto article (outdoor)
- Article category AC7 Metal articles
- Application of the substance / the mixture  
See our technical datasheet for application of this product.  
curing component of a two-component primer
- 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:  
W.Heeren & Zoon bv.  
Oosteinderweg 32  
1432 AL Aalsmeer  
Netherlands  
tel.+31 297-360366  
email: info@epifanes.nl
- Further information obtainable from: Research & Development.
- 1.4 Emergency telephone number: +61 7 5563 1222 (Monday-Friday 8:30am-5:00pm)

**SECTION 2: Hazards identification**

- 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3

H226 Flammable liquid and vapour.



health hazard

STOT RE 2

H373 May cause damage to the hearing organs through prolonged or repeated exposure.



corrosion

Eye Dam. 1

H318 Causes serious eye damage.

(Contd. on page 2)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 1)



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

STOT SE 3

H335 May cause respiratory irritation.

- 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008  
The product is classified and labelled according to the GB CLP regulation.
- Hazard pictograms



GHS02



GHS05



GHS07



GHS08



GHS09

- Signal word Danger
- Hazard-determining components of labelling:  
Fatty acids, C18-unsaturated, dimers, polymers with triethylenetetramine  
Xylene  
3,6-diazaoctanethylenediamin  
Ethylbenzene
- Hazard statements  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H373 May cause damage to the hearing organs through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.
- Precautionary statements  
P102 Keep out of reach of children.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 2)

- 2.3 Other hazards
- Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.

**SECTION 3: Composition/information on ingredients**

- 3.2 Mixtures
- Description:  
Resin mixture  
Solvent mixture with additives

· Dangerous components:

CAS: 103758-99-2 NLP: 500-290-3 Reg.nr.: 01-2119978243-32	Fatty acids, C18-unsaturated, dimers, polymers with triethylenetetramine --- ☠ Eye Dam. 1, H318 ☠ Aquatic Chronic 2, H411 ☠ Skin Irrit. 2, H315; Skin Sens. 1, H317	25-50%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene --- ☠ Flam. Liq. 3, H226 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ☠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	Ethylbenzene --- ☠ Flam. Liq. 2, H225 ☠ STOT RE 2, H373; Asp. Tox. 1, H304 ☠ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	≥2.5-<10%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol --- ☠ Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	≥2.5-<10%
CAS: 112-24-3 EINECS: 203-950-6 Index number: 612-059-00-5	3,6-diazaoctanethylenediamin --- ☠ Skin Corr. 1B, H314 ☠ Acute Tox. 4, H312; Skin Sens. 1, H317 ☠ Aquatic Chronic 3, H412	≥1-<2.5%

· Additional information:

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.

(Contd. on page 4)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 3)

- After inhalation:  
Supply fresh air and to be sure call for a doctor.  
In case of unconsciousness place patient stably in side position for transportation.
- After skin contact:  
Immediately wash with water and soap and rinse thoroughly.  
Immediately rinse with water.
- After eye contact:  
Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed  
No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed  
No further relevant information available.

\* **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media  
Suitable extinguishing agents:  
CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture  
During heating or in case of fire poisonous gases are produced.  
No further relevant information available.
- 5.3 Advice for firefighters  
Protective equipment: Mouth respiratory protective device.

\* **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures  
Wear protective clothing.  
Ensure adequate ventilation  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:  
Prevent seepage into sewage system, workpits and cellars.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
- 6.4 Reference to other sections  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.

(Contd. on page 5)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

See Section 13 for disposal information.

(Contd. of page 4)

**SECTION 7: Handling and storage**

- 7.1 Precautions for safe handling  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- Information about fire - and explosion protection:  
Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.  
Keep respiratory protective device available.
- 7.2 Conditions for safe storage, including any incompatibilities
- Storage:  
Requirements to be met by storerooms and receptacles:  
Store only in the original receptacle.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- 7.3 Specific end use(s) No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

- 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

1330-20-7 Xylene

WEL	Short-term value: 441 mg/m <sup>3</sup> , 100 ppm Long-term value: 220 mg/m <sup>3</sup> , 50 ppm Sk; BMGV
-----	--

100-41-4 Ethylbenzene

WEL	Short-term value: 552 mg/m <sup>3</sup> , 125 ppm Long-term value: 441 mg/m <sup>3</sup> , 100 ppm Sk
-----	---

- Regulatory information WEL: EH40/2020
- DNEL (Derived No Effect Level) voor professionals

103758-99-2 Fatty acids, C18-unsaturated, dimers, polymers with triethylenetetramine

Dermal	Long-term - systemic effects.	1.1 mg/kg/day (Employees)
Inhalative	Long-term - systemic effects.	3.9 mg/m <sup>3</sup> (Employees)

(Contd. on page 6)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 5)

## 1330-20-7 Xylene

Dermal	Long-term systemic effects.	212 mg//kg/day (Employees)
Inhalative	Acute / short term - local defects	442 mg/m <sup>3</sup> (Employees)
	Long-term - local effects.	221 mg/m <sup>3</sup> (Employees)
	Long-term - systemic effects.	221 mg/m <sup>3</sup> (Employees)

## 100-41-4 Ethylbenzene

Dermal	Long-term - systemic effects.	180 mg/kg/day (Employees)
Inhalative	Long-term - local effects.	293 mg/m <sup>3</sup> (Employees)
	Short-term systemic effects.	77 mg/m <sup>3</sup> (Employees)
	Long-term - systemic effects.	77 mg/m <sup>3</sup> (Employees)

## 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Dermal	Acute / short-term - systemic effects.	0.6 mg/kg bw/day (Employees)
Inhalative	Long-term - systemic effects.	0.15 mg/kg/day (Employees)
	Acute / short-term - systemic effects.	2.1 mg/m <sup>3</sup> (Employees)
	Long-term - systemic effects.	0.53 mg/m <sup>3</sup> (Employees)

## · DNEL (Derived No Effect Level) for general audience

## 103758-99-2 Fatty acids, C18-unsaturated, dimers, polymers with triethylenetetramine

Oral	Long-term systemic effects.	0.56 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	0.56 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.97 mg/m <sup>3</sup> (General population)

## 1330-20-7 Xylene

Oral	Long-term systemic effects.	12.5 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	125 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	65.3 mg/m <sup>3</sup> (General population)
	Long-term - local effects.	65.3 mg/m <sup>3</sup> (General population)
	Acute / short-term - systemic effects.	260 mg/m <sup>3</sup> (General population)
	Acute / short-term - local effects.	260 mg/m <sup>3</sup> (General population)

## 100-41-4 Ethylbenzene

Oral	Long-term systemic effects.	1.6 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	15 mg/m <sup>3</sup> (General population)

(Contd. on page 7)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 6)

## 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Oral	Long-term systemic effects.	0.075 mg/kg bw/day (General population)
Dermal	Long-term - systemic effects.	0.075 mg/kg bw/day (General population)
	Acute / short-term - local effects.	0.075 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects.	0.13 mg/m <sup>3</sup> (General population)
	Acute / short-term - systemic effects.	0.13 mg/m <sup>3</sup> (General population)

## PNECs

## 103758-99-2 Fatty acids, C18-unsaturated, dimers, polymers with triethylenetetramine

Freshwater	0.004 mg/l (Freshwater)
Marine water	0 mg/l (Marine water)
Sediment (freshwater)	434.02 mg/kg sed dw (Freshwater)
Sediment (marine water)	43.4 mg/kg sed dw (Marine water)
STP	3.84 mg/l (Segmentation, Targeting and Positioning)
Soil	86.78 mg/kg (soil)

## 1330-20-7 Xylene

Freshwater	0.327 mg/l (Freshwater)
Marine water	0.327 mg/l (Marine water)
Sediment (freshwater)	12.46 mg/kg sed dw (Freshwater)
Sediment (marine water)	12.46 mg/kg sed dw (Marine water)
STP	6.58 mg/l (Segmentation, Targeting and Positioning)
Soil	2.31 mg/kg (soil)

## 100-41-4 Ethylbenzene

Freshwater	0.1 mg/l (Freshwater)
Marine water	0.01 mg/l (Marine water)
Sediment (freshwater)	13.7 mg/kg sed dw (Freshwater)
Sediment (marine water)	1.37 mg/kg sed dw (Marine water)
STP	9.6 mg/l (Segmentation, Targeting and Positioning)
Soil	2.68 mg/kg (soil)

## 90-72-2 2,4,6-tris(dimethylaminomethyl)phenol

Freshwater	0.046 mg/l (Freshwater)
Marine water	0.005 mg/l (Marine water)
Sediment (freshwater)	0.262 mg/kg sed dw (Freshwater)
Sediment (marine water)	0.026 mg/kg sed dw (Marine water)
STP	0.2 mg/l (Segmentation, Targeting and Positioning)
Soil	0.025 mg/kg (soil)

(Contd. on page 8)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 7)

· Ingredients with biological limit values:

1330-20-7 Xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

- Additional information: The lists valid during the making were used as basis.
- 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Avoid contact with the skin.  
Avoid contact with the eyes and skin.
- Respiratory protection:  
Suitable respiratory protective device recommended.  
Filter AX  
In case of short or low load, breathing filter device; in the case of intensive or prolonged exposure, use a breathing apparatus independent of the surrounding air. A half-face mask for organic vapours and solvents according to EN140 type A1 or A2 is recommended.
- Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Butyl rubber, BR

(Contd. on page 9)



Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 8)

- Eye/face protection



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

- 9.1 Information on basic physical and chemical properties
  - General Information
  - Physical state Fluid
  - Colour: According to product specification
  - Odour: Characteristic
  - Odour threshold: Not determined.
  - Melting point/freezing point: Undetermined.
  - Boiling point or initial boiling point and boiling range 136 °C (100-41-4 Ethylbenzene)
  - Flammability Flammable.
  - Lower and upper explosion limit
  - Lower: 1.1 Vol %
  - Upper: 7 Vol %
  - Flash point: 27 °C
  - Ignition temperature: 430 °C (100-41-4 Ethylbenzene)
  - Decomposition temperature: Not determined.
  - pH at 20 °C 10
  - Viscosity:
  - Kinematic viscosity Not determined.
  - Dynamic at 20 °C: 1,400 mPas
  - Solubility
  - water: Fully miscible.
  - Partition coefficient n-octanol/water (log value) Not determined.
  - Vapour pressure: Not determined.
  - Density and/or relative density
  - Density at 20 °C: 0.916 g/cm<sup>3</sup>
  - Relative density Not determined.
  - Vapour density Not determined.

- 9.2 Other information
  - Appearance:
  - Form: Fluid
  - Important information on protection of health and environment, and on safety.
  - Auto-ignition temperature: Product is not selfigniting.
  - Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 10)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 9)

- Solvent content:
- Organic solvents: 49.8 %
- VOC content: 49.76 %
- VOC content:  
455.8 g/l / 3.80 lb/gal
- Solids content: 49.0 % (VB% 1h150 C)
- Change in condition
- Evaporation rate Not determined.

- Information with regard to physical hazard classes
- Explosives Void
- Flammable gases Void
- Aerosols Void
- Oxidising gases Void
- Gases under pressure Void
- Flammable liquids Flammable liquid and vapour.
- Flammable solids Void
- Self-reactive substances and mixtures Void
- Pyrophoric liquids Void
- Pyrophoric solids Void
- Self-heating substances and mixtures Void
- Substances and mixtures, which emit flammable gases in contact with water Void
- Oxidising liquids Void
- Oxidising solids Void
- Organic peroxides Void
- Corrosive to metals Void
- Desensitised explosives Void

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:  
No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products:  
No dangerous decomposition products known.

**SECTION 11: Toxicological information**

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- Acute toxicity  
Based on available data, the classification criteria are not met.

(Contd. on page 11)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 10)

· LD/LC50 values relevant for classification:		
1330-20-7 Xylene		
Dermal	Short-term exposure (15 minutes): 100 ppm	442 mg/m <sup>3</sup> (Occupational exposure limits)
	Long-term exposure (8 hours TWA): 50 ppm	221 mg/m <sup>3</sup> (Occupational exposure limits)
100-41-4 Ethylbenzene		
Oral	LD50	3,500 mg/kg bw (rat)
Dermal	LD50	17,800 mg/kg bw (rabbit)
112-24-3 3,6-diazaoctanethylenediamin		
Oral	LD50	2,500 mg/kg bw (rat)
Dermal	LD50	805 mg/kg bw (rabbit)

- Skin corrosion/irritation Causes skin irritation.
- Serious eye damage/irritation Causes serious eye damage.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- STOT-single exposure May cause respiratory irritation.
- STOT-repeated exposure  
May cause damage to the hearing organs through prolonged or repeated exposure.
- 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

**SECTION 12: Ecological information**

- 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties  
The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- Remark: Toxic for fish
- Additional ecological information:
- General notes:  
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Must not reach sewage water or drainage ditch undiluted or unneutralised.  
Danger to drinking water if even small quantities leak into the ground.  
Also poisonous for fish and plankton in water bodies.  
Toxic for aquatic organisms

GB

(Contd. on page 12)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)



(Contd. of page 11)



**SECTION 13: Disposal considerations**


- 13.1 Waste treatment methods
- Recommendation  
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents:  
Water, if necessary together with cleansing agents.

**SECTION 14: Transport information**

- 14.1 UN number or ID number  
· ADR, IMDG, IATA UN1263
- 14.2 UN proper shipping name  
· ADR 1263 PAINT, ENVIRONMENTALLY HAZARDOUS  
· IMDG PAINT, MARINE POLLUTANT  
· IATA PAINT
- 14.3 Transport hazard class(es)
- ADR
 

		
· Class		3 (F1) Flammable liquids.
· Label		3
- IMDG
 

		
· Class		3 Flammable liquids.
· Label		3
- IATA
 

		
· Class		3 Flammable liquids.
· Label		3
- 14.4 Packing group  
· ADR, IMDG, IATA III
- 14.5 Environmental hazards: Product contains environmentally hazardous substances: Fatty acids, C18-

(Contd. on page 13)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 12)

·	unsaturated, dimers, polymers with triethylenetetramine
· Marine pollutant:	No
· Special marking (ADR):	Symbol (fish and tree)
	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, S-E
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E
· Remarks:	> 450 l: 3 F1, III
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· Remarks:	> 30 l: 3, III
· UN "Model Regulation":	UN 1263 PAINT, 3, III, ENVIRONMENTALLY HAZARDOUS

**SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- Named dangerous substances - ANNEX I None of the ingredients is listed.
- Seveso category  
E2 Hazardous to the Aquatic Environment  
P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements  
200 t

(Contd. on page 14)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 13)

- Qualifying quantity (tonnes) for the application of upper-tier requirements  
500 t

- National regulations:

- Technical instructions (air):

Class	Share in %
NK	25-50

- Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- 15.2 Chemical safety assessment:  
A Chemical Safety Assessment has not been carried out.

**SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

- Department issuing SDS: Research & Development.

- Contact: J.J. van Dijk, tel: +31 297 360678, email: rend@epifanes.nl

- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 15)

Safety data sheet  
according to 1907/2006/EC, Article 31

Printing date 17.02.2023

Version number 16 (replaces version 15)

Revision: 07.12.2022

Trade name: Epifanes Epoxy Primer Comp. B (cure)

(Contd. of page 14)

Flam. Liq. 2: Flammable liquids - Category 2  
Flam. Liq. 3: Flammable liquids - Category 3  
Acute Tox. 4: Acute toxicity - Category 4  
Skin Corr. 1B: Skin corrosion/irritation - Category 1B  
Skin Irrit. 2: Skin corrosion/irritation - Category 2  
Eye Dam. 1: Serious eye damage/eye irritation - Category 1  
Eye Irrit. 2: Serious eye damage/eye irritation - Category 2  
Skin Sens. 1: Skin sensitisation - Category 1  
STOT SE 3: Specific target organ toxicity (single exposure) - Category 3  
STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2  
Asp. Tox. 1: Aspiration hazard - Category 1  
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2  
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3  
· \* Data compared to the previous version altered.

GB